



HEAT PIPE HEAT EXCHANGER
[SIDE MOUNT]



適用機械種類

- 基地台電控箱
- CNC 車床
- CNC 綜合立、臥式加工中心機
- CNC 龍門磨床、銑床
- CNC 線切割機
- CNC 專用機械
- CNC 儀器箱

APPLICATION

- Electrical control panel for base station
- CNC lathe
- CNC vertical & horizontal machine center
- CNC double column grinding and milling machine
- CNC wire cutting machine
- CNC specially made machine
- CNC instrument box

特性及功能

- 高效率熱交換器採用密閉型設計，內外空氣不產生對流。
- 可阻隔濕氣、油氣、粉塵進入電控箱內。
- 熱管式熱交換器是一種節約能源且效率高的傳熱導體，約為銅的1600倍，安全性高。
- 簡化輕巧之設計不佔空間，安裝容易，保養簡單。

FEATURE

- Handy and efficient heat exchanger. Enclosed design ensures no exchange of internal and ambient air.
- Prevent dust, humidity and moisture from entering into the electrical control panel.
- Heat pipe heat exchanger is an energy saving and high-efficiency heat conductivity. Heat conductivity is 1600 times of copper.
- It's easy to install and be simple design.

規格表

EA SERIES SPECIFICATION

型式 Model		EA-01A	EA-02A	EA-03A	EA-04A	EA-05A	EA-06A	EA-07A	EA-10A	EA-14A
熱交換量 Quantity of heat exchange	W	100	200	300	400	500	600	700	1000	1400
定格能力 Fix absorb heat quantity	W/°C	5	10	15	20	25	30	35	50	55
電源 Power source	V	1ø AC110V or AC220V 0/60HZ								
風扇電力 Fan rated power	W	50	50	72	72	72	72	72	144	144
開孔尺寸 Hole size	mm	216x245	210x280	215x370	190x314	260x370	290x320	260x410	368x450	400x460
外型尺寸 Dimension (DxWxH)	mm	70x250x480	65x250x580	82x250x780	90x225x655	91x295x780	90x340x655	100x295x858	12955x415x9	120x440x970
總重量 Weight	kg	6	7	10	10	11	11	13.4	40	22

EA-□□



AR 內掛 Internal type, AF 外掛 External type
熱交換量 Quantity of heat exchange capacity
掛壁式電控箱專用熱交換器 Heat pipe heat exchanger (side mount)

週圍溫度：
Room temperature: 35°C ↓