



AIR COOLING FOR OIL COOLER AND WATER CHILLER

AO/AW SERIES



適用機械種類

- CNC 車床油壓系統
- 各類點機械油壓箱冷卻
- 各類點焊機械
- 印刷機
- 光學儀器
- 醫療儀器
- 高週波機

APPLICATION

- Oil hydraulic system of CNC lathe
- Various oil hydraulic
- Various welding machine
- Printing machine
- Optical instrument
- Medical instrument
- High-cycle machine

特性及功能

- 可以降低液溫，避免溫度過高造成油裂化。
- 防止點焊機槍頭過熱損壞。
- 構造簡單，保養容易，可增加儀器試驗穩定度。
- 可保護槍頭使用壽命，提高效率，降低成本。

FEATURE

- Reduce oil temperature and maintain oil viscosity.
- Prevent overheating that might cause damage to the welding head.
- It's easy to maintain and be simple design. Ensure testing instrument reading stability.
- Improve welding efficiency and cost down.

規格表

AO/AW SERIES SPECIFICATION

型式 Model		AO-08	AO-15	AO-15PT	AO-24
電源 Power source	V	1ø AC220V 50/60HZ			
耗用電流 Total consumption	A	0.3	0.5	2.1	0.8
馬達泵浦 Pump	KCAL/H			1/4	
散熱氣噸位 Condenser ton	RT	1/2	1-1/3	1-1/3	2
幫浦流量 Pump discharge rate	l/min			7.5	
外型尺寸 Dimension (DxWxH)	mm	270x275x265	350x370x310	670x375x540	710x380x388
油箱 Oil tank	T			32	
配管口徑 Pipe size	inch	1/4"x1/4"	3/4"x3/4"	1/2"x1/2"	1"x1"
重量 Weight	kg	6	10	40	23



型式 Model		AW-08PT	AW-24PT	AW-60PT
電源 Power source	V	1ø AC220V 50/60HZ		
耗用電流 Total consumption	A	3ø AC220V	50/60HZ	
散熱器 Oil tank condenser	ton	1/2	1	3
馬達馬力 Motor horsepower	HP	1/2	3/4	1
風扇馬力 Fan horsepower	HP	1/6	1/2	3/4
幫浦流量 Pump discharge rate	l/min	20	30	40
膨脹水箱 Water tank	l/min	40	40	60
負荷電流 Rated current	A	3.3	6	8
配管口徑 Pipe size	inch	1/2"x1/2"	1"x1"	1"x1"
外型尺寸 Dimension (DxWxH)	mm	360x460x415	520x556x1029	805x605x1194
重量 Weight	kg	34	85	115

